



CP.LADY



100%
Made in Italy



APPLICATION

1 road barrier series LADY, LADY.5

CONTROL UNIT POWER SUPPLY

100/250 Vac – 50/60 Hz

MOTORS POWER SUPPLY

24 Vdc 220W

MAIN FUNCTIONS

Integrated LCD display | Integrated 433.92 MHz 64-code radio receiver with 3 encoding systems (Advanced Rolling Code, Rolling Code, Fixed Code) | Removable terminal boards | Automatic, semi-automatic and deadman's logic | Motor limit switch inputs | Open, close, step by step, pedestrian and stop inputs | Output for LADY.L accessory, LED integrated on arm | Output configurable as open barrier indicator light, second radio channel of incorporated receiver, arm light, service light, photocell test or maintenance indicator | Predesigned for the operation of opposed barriers with SIS synchronisation board (optional) | Autosetting of operation parameters | Anti-crushing safety thanks to amperometric obstacle detection | Adjustable slow-downs | Number of maneuvers | Programming access password | Maintenance warning | **Integrated battery charger, compatible with battery models DA.BT2/DA.BT6**



SIS

Quick connection electronic board that allows synchronised movement of 2 automation devices (opposed barriers). One board for each motor is necessary.



DA.2S

Electronic board that allows synchronised movement of 2 automation devices (opposed barriers).



DA.BT2

2.1Ah 12 Vdc Battery.

DA.BT6

7Ah 12 Vdc Battery.

AUTOMATISMI BENINCA SpA • Via del Capitello, 45 • 36066 Sandrigo (VI) ITALY • T +39 0444 751030 • sales@beninca.com

